

RUUD SALES FACT SHEET

Equipped with the Award Winning Comfort Control System™

- Increased Reliability
- On-Board Diagnostics
- Fault Recall
- Active Protection™



R-410A
earth friendly refrigerant



UPRL- JEZ

Two-Stage Four Models

Efficiencies ranging up to
17 SEER in certain matched systems.
Nominal Sizes 2, 3, 4 & 5 Tons
[7.03, 10.5, 14 & 17.6 kW]

GENERAL TERMS OF LIMITED WARRANTY*

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable periods stated, in accordance with the terms of the limited warranty.

Limited Warranty Coverage:

Ruud Ultra Series® equipment features a 10-year limited parts warranty.* In addition a 10-year conditional unit replacement warranty is provided. See Ruud Ultra Series® Warranty Card for details.

*This 10-year limited parts warranty is applicable only to single-phase products installed in residential applications. For complete details of the limited warranty, including applicable terms & conditions, see your local installer or contact the manufacturer for a copy.

RUUD ULTRA® Series

Features

The Ruud Ultra Series® UPRL- JEZ Two-Stage Heat Pump Outdoor Units can provide year-round heating and cooling comfort for residential, multi-family and light commercial applications. They are designed to operate with Ruud indoor units with cooling and heating capacities certified under the ARI Certification program.

- The *Comfort Control System™* provides on-board diagnostics and fault history for heat pump units with single-phase compressors by detecting system and electrical problems without adding sensors. It can also communicate "fault codes" to enabled "L terminal" thermostats. The integrated diagnostics with *Active Protection™* prevents compressor operation when damage would occur.
- 7-Segment LED Display is exclusive only to Ruud products. The information-display quickly and accurately shows technicians the source of malfunctions.
- Ten-year conditional unit replacement warranty.
- Compressor sound blanket is standard to provide quiet operation.
- Attractive, louvered wrap-around jacket protects coil from weather extremes and yard hazards. Top grille is steel reinforced for extra strength. Cabinet is powder painted for all weather protection.
- Exclusive Combination Grille/Motor Mount secures the fan motor to the underside of the discharge grille. The grille protects the motor windings and bearings from rain and snow.
- All controls are accessible by removing one service panel. Removable top grille provides access to the outdoor fan motor and outdoor coil.
- Compressor compartment offers additional protection from the elements and reduces operating noise.
- GE® ECM® fan motor is designed for low speed, quieter, energy-saving operation.
- Non-cycling reversing valve and demand defrost.
- All models meet or exceed a 1000-hour salt spray test per ASTM B117 Standard Practice for Operating Salt Spray Testing Apparatus.
- Dependable Copeland® Two-Stage Scroll® Compressor for precise temperature control providing ultimate comfort.
- Dual-Fuel capable with select thermostats.

U	P	R	L	—	024	J	E	Z
RUUD	REMOTE HEAT PUMP	EFFICIENCY R = 16 SEER	DESIGN SERIES L = R-410A		COOLING CAPACITY	ELECTRICAL DESIGNATION J = 208/230V-1-60	VARIATIONS E = EQUIPPED WITH THE COMFORT CONTROL SYSTEM™	COOLING CONNECTION FITTING Z = SWEAT W/SCROLL
024 = 24,000 BTU/HR [7.03 kW] 036 = 36,000 BTU/HR [10.55 kW] 048 = 48,000 BTU/HR [14.07 kW] 060 = 60,000 BTU/HR [17.58 kW]						Price Starting at: \$		

